

TEMP&RH DATA LOGGER



CE EN12830

APPLICATIONS



Vaccine transportation



Blood transport



Pharmaceutical



Fruit and vegetable transportation



Containerized shipment



Built-in USB connector

Data can be easily downloaded



Magnetic holder

Easy and quick fixing of equipment position



Automatic data generation

Automatically generates PDF report and CSV file



Intuitive LCD indication

LCD presents all key information including recording statistics, alarm and running status

TEMP&RH DATA LOGGER




HOW TempU07TH WORKS




Press the button to start



Put into the refrigerator



Logging temp & RH



Connect PC to get PDF/CSV report

SPECIFICATION

TempU07TH

Dimensions	100mm x 43mm x 12mm
Weight	54g
Waterproof Level	IP65
Measuring Range	Humidity: 5%~95%RH, Temp: -30°C ~ +70°C
Accuracy	±3%RH; ±0.3°C
Alarm Rang	Programmable high or low alarm limit for each channel [Default: <2°C or >8°C, <40%RH or >80%RH]
Memory Capacity	34560pcs
Start Mode	Button Start or Timed Start
Resolution	0.1%RH typically, 0.1°C
Usage	Multiple times
Battery Life	More than 2 years (Normal temperature 25°C)
Recording Interval	10 seconds to 99 hours adjustable [Default: 10 minutes]
Start Delay	Programmable (0~72 hours) [Default: 30 minutes]
Alarm Delay	Programmable (0~99 hours) [Default: 10 minutes]
Communication Interface	USB 2.0
Form of Report	PDF report and CSV file are optional(Default: PDF and CSV)

FEATURE

- The device has a magnetic holder
- Statistics available on LCD screen
- No software needed to export data
- Automatically generate PDF report and CSV file
- Programmable software for logging parameters, alarms, and start delay

Tzone Digital Technology Co., Ltd.

파인테크 www.finetech72.com
T. 070-8742-7727

